

HSM-CUP7 CUPPER HIGH SPEED LOGIC MODULE

The Systems Engineering HSM-CUP7 Copper High Speed Logic Module is an electronic upgrade which provides:

- ◇ **Reduced Tooling Damage:** by accurately detecting die jams/cup jams and immediately deactivating the clutch to prevent additional stroking.
- ◇ **Repeatable Air Strip Control:** to prevent air stripping and blow-out problems and thus reduce the occurrence of die jams or cup jams.
- ◇ **Accurate Clutch Control:** Incorporates TDC brake wear compensation algorithm to stop press at TDC regardless of actual brake response.
- ◇ **High Speed:** Module operates at speeds in excess of 300 Strokes Per Minute.



Features

- Performs high speed control functions of Cupper to speeds in excess of 300 Strokes Per Minute (machine mechanically permitting). This includes clutch control, air strip control, as well as die protection (die jam and cup jam detection).
 - Performs the following control functions:
 - Rapid response control of clutch/brake system for emergency stops (die protection) as well as precise TDC stops. **Note: The clutch solenoid outputs of the HSM-CUP7 are not intended as safety contacts for the cupper clutch and must not be the only interrupt to the clutch solenoids.**
 - Accurate die jam (no cup drop) and cup jam detection for up to 16-out presses.
 - Highly repeatable air strip control to reduce cup stripping and die jam problems.
 - Brake wear compensation (Auto TDC timing programming) algorithm to stop press at TDC regardless of brake response.
 - Brake response determination allows displaying of actual brake response (in degrees).
 - Brake response alarm to indicate when brake stopping response (in degrees) has exceeded user preset limit.
 - Lubricator speed reference (0-10volt analog output) provides reference to lubricator proportional to speed of cupper (user scalable).
 - Alarm detection: die jam detection, cup jam detection, scrap jam detection, timing signal fail detection, clutch output failure detection, no ram motion alarm, resolver failure detection, and brake response too long.
 - Data Acquisition: Total number of strokes and total number of die jam/cup jam faults for each station (for both current and last shift).
 - Can be used on virtually all types of Cupping Presses.
-

General Description

The HSM-CUP7 Cupper high speed logic module is an electronic upgrade for Cupping Presses which performs the high speed control functions of the cupper including: rapid response clutch/brake control, accurate die jam/cup jam detection, and precise air strip control. In addition, the module provides a brake wear compensation feature which automatically adjusts the TDC timing signal to stop the press at TDC regardless of brake stopping response. The module also provides a lubricator speed reference output, alarm detection, and data collection.

The module is not a dedicated “black box”, but instead is implemented using the high performance Systems M4503 PLC/PLS module which allows easy customization by either SEA or the end user. The module incorporates a built-in PLS which interfaces directly with the machine mounted resolver and provides all machine timing, eliminating the need for an external PLS. The HSM-CUP7 contains an integrated keypad and display which can be used by the operator to view collected data and can be used by authorized personnel (passcode or key switch protected) to adjust the timing and all setup parameters.

Clutch / Brake Control

The clutch/brake solenoids of the Cupper are activated by the HSM-CUP7 through the electro-mechanical two hand safety control circuitry provided externally by the user. The fast 0.5millisecond throughput of the HSM-CUP7 along with the fact that the PLS is fully integrated in the module, allows extremely fast and repeatable de-clutching and braking response to be achieved. Normally the clutch is controlled via inputs to the HSM-CUP7 that are mapped from outputs on the host PLC. However, detection of any of the alarms (die jam, cup jam, scrap jam, etc.) results in an immediate de-clutch of the solenoids.

Air Strip Control

The HSM-CUP7 provides a repeatability of 0.5 milliseconds for the air strip control thus reducing can stripping and blow-out problems. An “Air Strip (Low)”, “Air Strip (Mid)”, and “Air Strip (High)” timing signals are provided to activate the air strip when running in the respective speeds. These air strip timing signals can be adjusted independently to optimize air strip at all speeds.



Brake Wear Compensation

The HSM-CUP7 incorporates a brake wear compensation or automatic TDC timing feature which stops the press at TDC regardless of the actual braking response of the clutch/brake. The stopping compensation is accomplished by automatically adjusting the TDC timing signal based on the previous stop. Any overrun is detected and a new TDC timing signal is computed such that the machine will stop at the desired location on the next stop. Three TDC signals are provided: one for low, mid, and high speed. The mid and high TDC timing signals incorporate the brake wear compensation feature.

In addition to the brake wear compensation, the HSM-CUP7 also calculates the actual brake response (in degrees). This can then be displayed by the operator or maintenance personnel to determine the condition of the brake.

Die Protection (Die Jam / Cup Jam)

The “Cup Drop Window” timing signal, along with the machine mounted cup drop sensors, is used to verify that the cups do drop correctly from the machine. The cups must drop inside the “Cup Drop Window” in order to avoid a *Die Jam* alarm and the cups must not drop outside the “Cup Drop Window” in order to avoid a *Cup Jam* alarm. Die protection is provided for up to 16-out presses. The clutch is immediately de-activated for a TDC stop at the detection of either alarm.

Alarm Detection

In addition to the *Die Jam* and *Cup Jam* alarms, the module detects the following alarms: *Scrap Jam*, *Timing Signal Fail*, *Clutch Output Failure*, *No Ram Motion Detected*, *Resolver Failure*, and *Brake Response Too Long*. The *Scrap Jam* alarm occurs if scrap is detected backed up at the grounded scrap discharge. The *Timing Signal Fail* occurs when any of the timing signals generated in the PLS section fail to change state periodically while the machine is running. The *Clutch Output Fail* alarm occurs if either clutch output fails “on” or “off”. *No Ram Motion* occurs if no motion is detected after the clutch is activated. The *Resolver Failure* alarm occurs if motion is detected after the clutch is de-activated. The above alarms immediately deactivate the clutch when any one occurs with the respective alarm message displayed on the HSM-CUP7. These alarms are summed into one output that indicates to the host PLC that an alarm did occur.

Data Collection

The following data is collected for both the current shift and the previous (last) shift: Total number of strokes, total number of die jams/cup jams, and total number of die jams/cup jams per station. This data can be viewed locally on the display of the HSM-CUP7 by either the operator or production control personnel. This information is updated (“current” shift transferred to “last” shift) based on the change of state of a discrete input.

Specifications

Power Requirements:

Voltage: 100-240VAC, 50/60HZ
Current: 0.5 Amps @ 115VAC
0.25 Amps @ 230VAC

Temperature Ranges:

Operating: 0 to 55°C
Storage: 0 to 70°C

Resolver Interface:

Resolver Type: Systems Electronics Group RSV34-MS1 or equivalent (also can be paralleled with existing resolver/PLS)

Resolver Cable: Systems Electronics Group RSV-RSCBLE-XX

Control Inputs:

Voltage Range: 10-30VDC
Input “On” Voltage (min): 10.0 volts
Input “On” Voltage (max): 30.0 volts
Input “Off” Voltage (max): 5.0 volts
Input Current (max): 15 milliamps @ Vin=30V
Optical Isolation: 1500 Vrms

Outputs:

Voltage Range: 10-30VDC
Output “On” Voltage (min): VCC-2.00 volts
Output “On” Voltage (max): VCC-0.25 volts
Output “Off” Voltage (max): 1.5 volts
Output “On” Current (max-cont): 0.5 Amps DC
Output “On” Current (100msec): 3.0 Amps DC
Optical Isolation: 1500 Vrms



Ordering Information

The HSM-CUP7 module is provided for door mounting on the user's control cabinet door or console. The order number for the HSM-CUP7 is as follows:

<u>Part Number</u>	<u>Description</u>
HSM-CUP7	Copper high speed logic module which includes the following: 1ea. HSM-CUP7 module (M4503 with required I/O boards) 1ea. HSM-CUP7 User's Manual 1ea. HSM-CUP7 Keypad Quick Reference Manual 1ea. HSM-CUP7 Program Disk 1ea. M4500 User's Manual

HSM-CUP7 Options (purchased separately)

The following items can be purchased separately as required or desired:

<u>Part Number</u>	<u>Description</u>
HSL-DSP	Remote RPM/Position Display
RSV34-MS1	Resolver (required if machine is not already equipped with resolver)
RSV-RSCBLE-XX	Resolver Cable

Dimensions

